



L94 Antistatic

Flexible hose made of a special polyamide fabric, double antistatic PVC-coating with high mechanical strength, embedded steel wire helix.

TECHNICAL SPECIFICATIONS AND USAGE LIMIT							
COLOR	LENGTH	PRODUCTION DIAMETERS	FIRE REACTION	ANTISTATICITY	WORKING TEMPERATURE	CURVATURE RADIUS	AXIAL COM-PRESSIBILITY
Black	10 m. standard (up to 20 m on request)	from 40 to 800 mm	<100 mm DIN 75200	$R \leq 10^8 \Omega$	-20°C +90°C (peak +110°C)	0,9 x $\varnothing$	5:1

PRODUCTION DIAMETERS																	
40	45*	50	55*	60	63	65*	70	76	80	82	90	100	110	120	125	130	140
150	160	180	200	225*	250	275*	300	315	350	400	450*	500	550*	600	700	800	

*Diameters available on request.
Diameters other than those indicated are available by prior feasibility check.

MAIN APPLICATIONS

Suction of light dust, fumes, gases, including corrosive. Suction of textile fibres and paper scraps. Connection to moving parts.

MAINTENANCE

Periodically check the state of wear of the hose and immediately replace it if damaged or broken. Pay maximum attention to the duct operating temperatures.

TECHNICAL DATA				
DIAMETERS	OPERATING PRESSURE	OPERATING VACUUM	INSIDE CURVATURE RADIUS	WEIGHT
[mm]	[bar]	[bar]	[mm]	[gr/m]
40	1,50	0,30	40	317
50	1,20	0,25	50	395
60	1,00	0,20	60	476
70	0,90	0,18	70	512
80	0,80	0,10	80	553
100	0,60	0,08	100	687

DIAMETERS	OPERATING PRESSURE	OPERATING VACUUM	INSIDE CURVATURE RADIUS	WEIGHT
[mm]	[bar]	[bar]	[mm]	[gr/m]
120	0,55	0,07	120	829
130	0,50	0,07	130	894
150	0,30	0,06	150	968
160	0,30	0,06	160	1026
180	0,23	0,05	180	1090
200	0,20	0,04	190	1212
250	0,15	0,03	220	1513
300	0,10	0,02	260	1815
350	0,06	0,02	310	2295
400	0,04	0,01	360	2621
450	0,04	0,01	390	3620
500	0,03	0,01	420	4021
550	0,03	0,01	450	4423
600	0,03	0,01	480	4824

Data given in this table are approximate.
* Pressure and vacuum data based on +20°C room temperature.

GREEN BUILDING

Thanks also to the support of GreenMap, products manufactured by Tecnica srl contribute to obtain the credits of the major international rating systems for sustainable buildings:



LEED	WELL	BREEAM
Contributes to credits: MR	Contributes to credits: MATERIALS	Contributes to credits: HEA
For further details regarding the specific contributions to the credits indicated, contact Tecnica Srl.		

APPLICATIONS								
OEM	Flexibility	Easy Pack	Self-extinguishing	Tear resistance	Calibrated diameters*	Certified REACH	Certified RoHS	Halogen free
						*on request		
Compact version*	Industry	Building	Non-magnetic*	Extractor Hoods	Temporary air conditioning			